

*Sub  
C1*  
computer system that changes the at least one identifier used by the operating system to enable access by the host computer to the at least one computer system resource, to alter a manner in which the at least one application program accesses the at least one computer system resource.

---

*Sub  
C1*  
45. (Amended) A computer readable medium encoded with a reconfiguration program for execution on a host computer in a computer system including the host computer and at least one computer system resource accessible to at least one application program executing on the host computer, wherein the host computer comprises an operating system and the operating system uses at least one identifier to enable access by the host computer to the at least one computer system resource, the reconfiguration program, when executed on the host computer, performs a method of reconfiguring the computer system, the method comprising a step of:

*2*  
A) dynamically reconfiguring the computer system, without reinitializing the host computer or the application program, in response to a change in a configuration of the computer system that changes the at least one identifier used by the operating system to enable access by the host computer to the at least one computer system resource, to alter a manner in which the at least one application program accesses the at least one computer system resource.

---

*Sub  
C1*  
72. (Amended) A host computer for use in a computer system including the host computer and at least one computer system resource accessible to at least one application program executing on the host computer, the host computer comprising:

*3*  
an operating system and the operating system uses at least one identifier to enable access by the host computer to the at least one computer system resource; and

at least one controller to dynamically reconfigure the computer system, without reinitializing the host computer or the application program, in response to a change in a configuration of the computer system that changes the at least one identifier used by the operating system to enable access by the host computer to the at least one computer